



**A CASE HISTORY**

# Anchors and Foundations for Telecom Industry

Site Owner: Centennial Communications

Tower Supplier:

Sabre Communications, Inc.

Location: South Bend, LA

Foundation Contractor:

Two-Way Communications, Inc.

Lafayette, LA

Tower Type : Guyed (5 Levels)  
 Tower Height : 300'-0"  
 Center (Base) Reactions:  
 Maximum Compression 142.0 kips\*  
 Maximum Groundline Shear 1.3 kips  
 \*Plus weight of concrete pile cap of 60.0 kips  
 Design Load/Guy wire: 93.4 kips  
 (7 Guy wires into a single termination point)

Soil Profile:  
 0 - 25' Soft clay  
 25' plus Firm clay

Center Piles:  
 12 Type HS with 35'-0" of plain extension  
 Ultimate Capacity (UCt) = UCb + UCf  
 UCt = 34.0 + 0.0 = 34.0 kips

Guy Anchors:  
 Six Type SS5 anchors per guy wire termination point. The six guy anchors were connected to the seven guy wires via a spreader beam and fan plate assembly.

Installation Equipment:  
 Case backhoe equipped with a 12,500 ft-lb drive motor with an internal torque-monitoring device  
 Track mounted rig equipped with a 12,500 ft-lb drive motor with an internal torque-monitoring device. Drive motor is located in a set of leads.



• Twelve HS piles and rebar for tower mast



• Installing guy anchors



• Seven guy wires to six SS anchors via dual spreaders and fan plate



[www.abchance.com](http://www.abchance.com)

A.B. Chance, a Division of Hubbell Power Systems, Inc.  
 210 N. Allen St.  
 Centralia, MO 65240  
 Phone: 573-682-8414  
 Fax: 573-682-8660

©2006 Hubbell  
 Printed in USA  
 RGS

ISO 9001:2000



Certificate No. 001136

Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.

Bulletin 02-0004 Rev. 3/06